

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0547220607](#)
Status: **Active**
Description: 0.50mm (.020") Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 1.50mm (.059") Stacking Height, Lower Circuit Size Version, 60 Circuits

Documents:

[3D Model](#) [Product Specification PS-54722-009 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family PCB Receptacles
Series [54722](#)
Application Board-to-Board, Signal
Comments Embossed Tape Reel Height: 380mm (14.961")
Product Name SlimStack™

Physical

Circuits (Loaded) 60
Glow-Wire Compliant No
Mated Height 1.50mm (.059")
Material - Metal Phosphor Bronze
Material - Plating Mating Gold
Material - Plating Termination Gold
Number of Rows 2
Orientation Vertical
PCB Locator No
PCB Retention None
PCB Thickness - Recommended 1.60mm (.063")
Packaging Type Embossed Tape on Reel
Pitch - Mating Interface 0.50mm (.020")
Polarized to PCB No
Surface Mount Compatible (SMC) N/A
Temperature Range - Operating -25°C to +85°C
Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 0.5A
Voltage - Maximum 50V

Material Info

Reference - Drawing Numbers

Product Specification PS-54722-009, RPS-54722-025, RPS-54722-026, RPS-54722-029, RPS-54722-030, RPS-54722-034
Sales Drawing SD-54722-007, SD-54722-008




image - Reference only

Series

EU RoHS

**ELV and RoHS
Compliant**

REACH SVHC

Not Reviewed

Low-Halogen Status

Low-Halogen

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[54722Series](#)

Mates With

[55560 PCB Header](#)