

## Europe connectors - EC 4 TR - 3240170

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Polyamide Europe terminal strip, transparent, for connecting solid conductors and stranded conductors with ferrules with a cross section of 0.5 to 4 mm<sup>2</sup>

### Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	19.41 GRM
Custom tariff number	85369010
Country of origin	Austria

### Technical data

#### General

Number of levels	1
Number of connections	24
Color	transparent
Insulating material	PA
Inflammability class according to UL 94	V2
Maximum load current (lower level)	32 A (with 4 mm <sup>2</sup> conductor cross section)
Nominal current I <sub>N</sub> (lower level)	32 A (with 4 mm <sup>2</sup> conductor cross section)
Nominal voltage U <sub>N</sub>	450 V
Maximum load current (upper level)	32 A (with 4 mm <sup>2</sup> conductor cross section)
Number of positions	12

#### Dimensions

Width	16.2 mm
Length	93.6 mm
Height	13.4 mm

#### Connection data

Connection method	Screw connection
-------------------	------------------

## Europe connectors - EC 4 TR - 3240170

### Technical data

#### Connection data

Conductor cross section solid min.	0,5 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	12
Conductor cross section stranded min.	0,5 mm <sup>2</sup>
Conductor cross section stranded max.	4 mm <sup>2</sup>
Min. AWG conductor cross section, stranded	20
Max. AWG conductor cross section, stranded	12
Conductor cross section stranded, with ferrule without plastic sleeve min.	0,5 mm <sup>2</sup>
Conductor cross section stranded, with ferrule without plastic sleeve max.	1,5 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve min.	0,5 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve max.	1 mm <sup>2</sup>
2 conductors with same cross section, solid min.	0,5 mm <sup>2</sup>
2 conductors with same cross section, solid max.	0,75 mm <sup>2</sup>
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	0,5 mm <sup>2</sup>
Stripping length	5 mm
Screw thread	M2,6
Tightening torque, min	0,4 Nm
Tightening torque max	0,5 Nm

### Classifications

#### eCl@ss

eCl@ss 4.0	27141106
eCl@ss 4.1	27141106
eCl@ss 5.0	27141106
eCl@ss 5.1	27141106
eCl@ss 6.0	27141106
eCl@ss 7.0	27141106
eCl@ss 8.0	27141106

#### ETIM

ETIM 3.0	EC001284
ETIM 4.0	EC001284
ETIM 5.0	EC001284

## Europe connectors - EC 4 TR - 3240170

### Classifications

#### UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

### Approvals

#### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / cULus Recognized

---


#### Ex Approvals


---

#### Approvals submitted

---

### Approval details

UL Recognized 			
	B	C	D
mm <sup>2</sup> /AWG/kcmil	22-12	22-12	22-12
Nominal current I <sub>N</sub>	20 A	20 A	20 A
Nominal voltage U <sub>N</sub>	300 V	300 V	300 V

cUL Recognized 			
	B	C	D
mm <sup>2</sup> /AWG/kcmil	22-12	22-12	22-12
Nominal current I <sub>N</sub>	20 A	20 A	20 A
Nominal voltage U <sub>N</sub>	300 V	300 V	300 V

## Europe connectors - EC 4 TR - 3240170

### Approvals

cULus Recognized 